

Pneumatic Valve



AD -20 Series

Product Range:

- * 3/2 Way Single Solenoid Valve
- * 5/2 Way Single Solenoid Valve
- * 5/2 Way Double Solenoid Valve
- * 5/3 Way (3 Position) Double Solenoid Valve
- * 3/2 Way Single Pilot Valve
- * 5/2 Way Single Pilot Valve
- * 5/2 Way Double Pilot Valve
- * 5/3 Way (3 Position) Double Pilot Valve
- * Manifold For 3/2 Valve
- * Manifold For 5/2 & 5/3 Valves

Technical Specifications :

- * Body : Aluminium Anodized
- * Seals : Nitrile
- * Design : Spool type, internal pilot operated(External Pilot on Request)
- * Media : Air (Filtered & Lubricated)
- * Size : 1/4" & 1/2" BSP (F)
- * Temperature : 5 to 55°C
- * Pressure Range : 1 to 10 kg/cm²
- * Leakage : Bubble Tight
- * Coil Voltage : 12V, 24V, 48V, 110V, 230V, (AC / DC)(Non Std. Voltage Available On Req.)
- * Duty Cycle : Continuous Rated
- * Response Time : 15 msec ON / 25 msec OFF
- * Protection : 65 Class F
- * Connector : DIN 43650 B

Poppet Solenoid Valve

Product Range:

3/2 Way Poppet Type Solenoid valve
Size: 1/2" to 1.1/2"

5/2 Way Poppet Type Single Solenoid valve
Size: 3/8" (Basic Body) : 1/4", 3/8", 1/2"
3/4" (Basic Body) : 1/2", 3/4", 1"

5/2 Way Poppet Type Double Solenoid valve
Size: 3/8" (Basic Body) : 1/4", 3/8", 1/2"
3/4" (Basic Body) : 1/2", 3/4", 1"

Poppet Type Solenoid Sugar Valve
Size : 1/4" to 1/2"



Technical Specifications:

Body: Aluminium

Seals: Nitrile Rubber

Design: Poppet Type Internal Pilot Operated, (Ext. Pilot on Req.)

Orifice: Refer to Technical Data

Ports: Refer to Technical Data

Weight: Refer to Technical Data

Operating Conditions:

Media: Air (Filtered & Lubricated)

Temperature: 5 to + 50°C

Pressure Range: 2.5 to 10 Kg/cm²

Leakage: Bubble Tight

Flow (NLMP) at 5 Bar: Refer to Technical Data.



RM Series

Features:

- * Heavy & Durable design.
- * Aluminium Die Cast Standard Grade with Powder Coating.
- * Hard Chrome Plated spool for rust free smooth and long-life cycle.
- * Coil – Continuous duty low power consumption, CIMFR & CE Approved.
- * Superior High-Grade Seals
- * Simple design easy to maintenance
- * Manual Operator Push, Rotate & Lockable type.



Siko Series

Features:

- » Compact Design
- » Aluminium Die Cast Standard Grade with Powder Coating.
- » Hard Chrome Plated spool for rust free smooth and long-life cycle.
- » Superior High-Grade Seals
- » Panel Mounting Available.