

## Ball Valve

### Pneumatic Rotary Actuator Operated 2 Piece Design “VGO” Ball Valve

#### Specifications:

**Model :** VGO

**Design :** 2 Piece Fire Safe & Floating Design  
Ball Valve

**Body :** WCB / CF8 / CF8M / CF3M

**Size :** ½” to 14”

**Ball :** CF8 / CF8M

**Seat :** PTFE / CFT / GFT / PEEK / TFM

**Temperature :** up to 180° C

**Pressure :** Up to 10 BAR

**End Connection :** Flanged End to ASME B 16.5  
150 Class, 300 Class (up to 1500# On Request).



### Pneumatic Rotary Actuator Operated 3 Piece Design Ball Valve

#### Specifications :

**Model :** OKS

**Design :** 3 Piece Design Ball Valve(Fire Safe Design  
Available )

**Body :** WCB / CF8 / CF8M / CF3M

**Size :** ½” to 14”

**Ball :** CF8 / CF8M / CF3M

**Seat :** PTFE / CFT / GFT / PEEK / TFM

**Temperature :** up to 180° C

**Pressure :** Up to 10 BAR

**End Connection :** Screwed End / Socket Weld / Tri  
clover / Flanged End Class 150#, 300#.



## Pneumatic Rotary Actuator Operated 3 Way / 4 Way / 5 Way Ball Valve

### Specifications :

**Model :** SUZ

**Design :** 3 Way-4 Way-5 Way Design Ball Valve For Multiple Diverting / Mixing Operation available in “T” Port / “L” Port / “X” Port in Full Bore / Reduce Bore

**Body :** WCB / CF8 / CF8M

**Size :** 1/2" to 6"

**Ball :** CF8 / CF8M

**Seat :** PTFE / GFT / CFT / PEEK / TFM

**Temperature :** up to 180 °C

**Pressure :** up to 10 BAR

**End Connection :** Screwed End To BSP/NPT, Socket Weld ,Triclover Ends, Flanged End To ASME B16.5 Class 150 / 300.

