

## Pneumatic Drum Type of Control Valve

### DNF Pneumatic Actuator Operated Drum Valve



#### Specifications

**Model:** DNF, **Body:** WCB / C.I. / CF8 / CF8M, **Size Range:** 2" to 24" Flanged End, **Piston:** Stainless Steel 304 / 316, **Seals:** NBR / Viton / EPDM, **Temperature:** 80 °C (For Water), 180 °C (For Steam), **Working Pressure:** up to 10 BAR, **End Connection:** Flanged End.

### DEF Electric Actuator Operated Drum Valve



#### Specifications

**Model:** DEF, **Body:** WCB / C.I. / CF8 / CF8M, **Size Range:** 2" to 24" Flanged End, **Piston:** Stainless Steel 304 / 316, **Seals:** NBR / Viton / EPDM, **Temperature:** 80 °C (For Water), 180 °C (For Steam), **Working Pressure:** up to 10 BAR, **End Connection:** Flanged End.

### DFS Solenoid Operated Drum Valve



#### Specifications

**Model:** DFS, **Body:** WCB / C.I. / CF8 / CF8M, **Size Range:** 2" to 24" Flanged End, **Piston:** Stainless Steel 304 / 316, **Seals:** NBR / Viton / EPDM, **Temperature:** 80 °C (For Water), 180 °C (For Steam), **Working Pressure:** up to 10 BAR, **End Connection:** Flanged End.