

Angle Valve

6212M



AVCON Manual Hand Operated Valves. Type 6212M are available in following configurations.1) BS6212MXX6: Spigot Weldable end to ASME BPE-2012. Sizes:15mm (½”) to 50mm (2”). Body and Bonnet: Standard-Investment castes-ASTM A351 CF8 (DIN1.4301) (SS-304). Optional-Investment casted CF8M(SS-316) (DIN1.4408) (GX6 Cr. Ni MO1810). Pressure Temp. Rating: As per ASME B-16.34. End Connection: Spigot end (As per ASME BPE -2012) . Seating: Standard-Soft seat PTFE backed by EPDM. Optional-VITON/EPDM/Buna Nitrile.

6612E



2/2 Way Pneumatic Piston Operated Normally Closed Valves. With Cylinder Actuator, Angle Type for On-Off Application (Rust Free Design) , SPECIFICATIONS: Sizes: 15 mm (1/2”) to 50 mm (2”).

6812M/6824M



2/2-Way Angled Metal Body Valve with Engineering Plastic-Piston Actuator. For On-Off Application (Rust Free Design), Normally Closed Type.6812M For Flow Over the Seat, 6824M For Flow Under the Seat. SPECIFICATIONS: Sizes:15mm (1/2”) to 50mm (2”). Construction: 6812M-NC-Flow over the seat. 6824M-NC-Flow under the seat. Body and Bonnet: Standard-Investment casted SS-ASTM A351 CF8 (DIN1.4301). Optional-Investment casted SS-ASTM A351CF8M (DIN1.4408) (GX6 Cr.Ni MO1810).