

## Ball Valves

### 2370F



**Metal Ball Valves Screwed & Flanged End – 2 Way with Pneumatic Rotary Actuator 2-Way, Full Port, Ball Valve, 3-Piece Design with Pneumatic Rotary Actuator. AVCON is producing 3-piece Ball Valve with ISO 5211 mounting pad. The valves are provided with mounting bracket, couplers for fitting Pneumatic Rotary Actuators, either Double Acting or Spring Return Type. (For Pneumatic Actuator details, please refer to AVCON leaflet ACT-Range). Flanged end valves having Face to face dimension as per DIN 3202-1-1984; also, DN/EN 558-1-1995. But for Screwed End Ball Valves, face to face dimensions as per this leaflet. Model 3400 Pneumatic Actuators having Namur mounting interface, are available with AVCON Namur 5-way, 2-**

**Position, Solenoid Valves type 9484E, 9384E, 9485E, 9385E.**

### 2330F/2331F – Three Way



**Metal Ball Valves Screwed & Flanged End – 3 Way with Pneumatic Actuator Full Port ('L' & 'T' Port) 3/2 Way Metal Body Ball Valves Pneumatic Actuators Full Port ('L' & 'T' Port). SPECIFICATIONS: Size: 15mm (1/2") to 65mm (2 1/2"). Body and End Piece: Investment Casted Cast Steel ASTM A216 WCB or Stainless Steel ASTM A351 CF8 (SS304) or CF8M (SS316).**

### 2390F



**Metal Ball Valves Screwed & Flanged End – 2 Way with Pneumatic Rotary Actuator 2- Way Full Port, 2 Piece Design with Pneumatic Rotary Actuator. (Available in Fire Safe & Non- Fire Safe Design) AVCON produces 2-way, 2-piece Ball Valves with ISO 5211 mounting pad. Valves can be provided with Direct Mount or Bracket mount couplers for fitting Pneumatic Rotary Actuators, either Double Acting or Spring Return type. For details of Pneumatic Actuators, please refer to AVCON Leaflet 'ACT'- Range Series. These Flanged end Ball Valves are having face to face dimensions as per DIN/EN 558-2012. Pneumatic Actuators having NAMUR mounting interface, are available with AVCON NAMUR 5-way, 2-Position Solenoid Valves Type 9484E, 9384E, 9485E and 9385E.**