

2-Way High Pressure Ball Valves

GE1, GE2

CARBON STEEL:

Type: ball valve 2 way. **Material:** 1,0737. **Sizes:** from DN6 up to DN13, DN25. **Ends:** BSP-NPT-SAE- DIN. **O-Rings:** NBR, FKM, EPDM, MVQ. **Pressure:** up to PN500. **Temp range:** -20°C to +100°C



STAINLESS STEEL:

Type: ball valve 2 way. **Material:** 1,4404. **Sizes:** from DN6 up to DN25. **Ends:** BSP-NPT-SAE-DIN. **O-Rings:** NBR, FKM, EPDM, MVQ. **Pressure:** up to PN500. **Temp range:** -30°C to +100°C

GM, GM1

CARBON STEEL:

Type: ball valve 2way. **Material:** 1,0570/1,4404. **Sizes:** from DN6 up to DN100. **Ends:** BSP-NPT-SW-SWXT -PE BW. **O-Rings:** NBR, FKM, EPDM, MVQ. **Pressure:** up to PN500 / S3000. Fire safe BS 6755. Antistatic device. **Temp range:** -46°C to +250°C



STAINLESS STEEL:

Type: ball valve 2way. **Material:** 1,4404. **Sizes:** from DN6 up to DN100. **Ends:** BSP-NPT-SW-SWXT -PE BW. **O-Rings:** NBR, FKM, EPDM, MVQ. **Pressure:** up to PN500 / S3000. Fire safe BS 6755. Antistatic device. **Temp range:** -30°C to +100°C.