

Air Line Valves

Flow Control Valve

Features:

- * Directly mountable on cylinder / valve ports
- * Can be rotated by 360°
- * Fine regulation of air flow
- * Nickel plated body
- * Male threads(R) Teflon coated
- * Elegant design and finish



Function:

These valves allow controlled flow of air in one direction and free flow in the other direction. These are available in two versions – a) Supply control version, and b) Exhaust control version.

Flow Control Valve Inline Type

Low control valve – Inline type

GR2 series (Sizes: Ø4, 6, 8, 10 & 12mm)

Features:

- * Fine regulation of air flow
- * Elegant design and finish
- * Available sizes: Ø4, 6, 8, 10 & 12mm



Flow Control Valve Metal GR

Features:

- * Directly mountable on cylinder
- * Fine regulation of air flow
- * Male threads (G) with sealing washer
- * Elegant design and finish
- * Slotted head screw adjusting type



Function:

These valves allow controlled flow of air in one direction and free flow in the other direction. These are available in two versions – a) Supply control version, and b) Exhaust control version

Inline Slide Valve

GS1 series (Sizes: R1/8, R1/4, R3/8, R1/2, R3/4)

Features:

- * Inline mounted
- * Sleeve type, saves space
- * Smooth, easy operation



Non-Return Valve

GV1 series (Sizes: G1/8, G1/4, G3/8, G1/2)

Features:

- * In line mounting
- * Low cracking and closing pressure
- * Bubble tight elastomer seat



OR Valve

GB series (Sizes: M5, G1/8, G1/4)

Features:

- * OR valve delivers air at the outlet (A) always supplied by higher pressure (X or Y)
- * If two signals of different pressure is applied, the higher pressure is connected to outlet (A)



Pilot Operated NRV

GV2 series (Sizes: G1/8, G1/4, G3/8, G1/2)

Features:

- * Available in two versions
- * Low cracking and closing pressure
- * Bubble tight – elastomer seat
- * Plastic portion can be turned by 360°
- * Teflon pre-coated male taper threads



Quick Exhaust Valve

GQ series (Sizes: M5, G1/8, G1/4, G3/8, G1/2)

Features:

- * Increase the speed of the cylinder
- * With / without silencer
- * Connection – M5, G1/8, G1/4, G3/8, G1/2
- * Type GQ01 series is with silencer to reduce the exhaust noise.

